

# THE Honey MODULE

## TSM-PD05

**60 CELL**  
MULTICRYSTALLINE MODULE

**255–270W**  
POWER OUTPUT RANGE

**16.5%**  
MAXIMUM EFFICIENCY

**0/+5W**  
POSITIVE POWER TOLERANCE

**TRINA SOLAR: A STRONG AND RELIABLE PARTNER**

As a leading global manufacturer of next generation photovoltaic products, Trina Solar is committed to building mutually beneficial alliances with installers, developers, distributors and technological partners as the backbone of our shared goal to drive Smart Energy Together. Thanks to an extensive sales and service network with local expert teams throughout Europe, Trina Solar is perfectly positioned to support your needs. With Trina Solar as your strong, bankable partner you can rest assured knowing that you've made the right choice.

[www.trinasolar.com](http://www.trinasolar.com)



**Excellent low light performance on cloudy days, mornings and evenings**

- Advanced surface texturing
- Back surface field
- Selective emitter



**Maximize Limited Space**

- 60-cell module power output up to 270W
- Up to 165 W/m<sup>2</sup> power density



**Highly reliable due to stringent quality control**

- All modules have to pass electroluminescence (EL) inspection
- Over 30 in-house tests (UV, TC, HF, and many more)
- In-house testing goes well beyond certification requirements
- PID resistant
- 1000 V UL/1000V IEC certified




**Certified to withstand challenging environmental conditions**


- 130 km/h wind load (2400 Pa)
- 900 kg snow load per module (5400 Pa)
- 35 mm hail stones at 97 km/h
- Ammonia resistance
- Salt mist resistance
- resistance to sand and dust abrasion

**LINEAR PERFORMANCE WARRANTY**


10 Year Product Warranty • 25 Year Linear Power Warranty



**DIMENSIONS OF PV MODULE TSM-PD05**  
(unit:mm)




Back View




A-A

**I-V CURVES OF PV MODULE (270W)**



**P-V CURVES OF PV MODULE (270W)**



**CERTIFICATION**

IEC61215/EN61215  
IEC61730/EN61730  
IEC 627162 PfG 1917/05.11  
IEC 61701  
DIN EN 60068-2-68 LC2  
MCS BRE PV0183

ELECTRICAL DATA @ STC	TSM-255 PD05	TSM-260 PD05	TSM-265 PD05	TSM-270 PD05
Peak Power Watts- $P_{MAX}$ (Wp)*	255	260	265	270
Power Output Tolerance- $P_{MAX}$ (W)	0/+5	0/+5	0/+5	0/+5
Maximum Power Voltage- $V_{MPP}$ (V)	30.5	30.6	30.8	30.9
Maximum Power Current- $I_{MPP}$ (A)	8.37	8.50	8.61	8.73
Open Circuit Voltage- $V_{OC}$ (V)	38.1	38.2	38.3	38.4
Short Circuit Current- $I_{SC}$ (A)	8.88	9.00	9.10	9.18
Module Efficiency $\eta_m$ (%)	15.6	15.9	16.2	16.5

STC: Irradiance 1000 W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5  
\* Measuring tolerance: ±3%

ELECTRICAL DATA @ NOCT	TSM-255 PD05	TSM-260 PD05	TSM-265 PD05	TSM-270 PD05
Maximum Power- $P_{MAX}$ (Wp)	189	193	197	200
Maximum Power Voltage- $U_{MPP}$ (V)	28.2	28.4	28.6	28.7
Maximum Power Current- $I_{MPP}$ (A)	6.71	6.81	6.89	6.97
Open Circuit Voltage- $U_{OC}$ (V)	35.3	35.4	35.5	35.5
Short Circuit Current- $I_{SC}$ (A)	7.17	7.27	7.35	7.41

NOCT: Irradiance at 800 W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1 m/s.

**MECHANICAL DATA**

Solar Cells	Multicrystalline 156 × 156 mm (6 inches)
Cell Orientation	60 cells (6 × 10)
Module Dimensions	1650 × 992 × 35 mm (65.0 × 39.1 × 1.38 inches)
Weight	18.6 kg
Glass	High Transparency, Anti-Reflective, AR Coated and Heat Tempered Solar Glass - 3.2 mm (0.13 inches)
Backsheet	White
Frame	Silver Anodized Aluminium Alloy
J-Box	IP 67 rated or IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm <sup>2</sup> (0.006 inches <sup>2</sup> ), 1000 mm (39.4 inches)
Connector	MC4 Compatible

**TEMPERATURE RATINGS**

Nominal Operating Cell Temperature (NOCT)	44°C (±2K)
Temperature Coefficient of $P_{MAX}$	- 0.41%/K
Temperature Coefficient of $V_{OC}$	- 0.32%/K
Temperature Coefficient of $I_{SC}$	0.05%/K

**MAXIMUM RATINGS**

Operational Temperature	-40 to +85°C
Maximum System Voltage	1000V DC (IEC) 1000V DC (UL)
Max Series Fuse Rating	15A
Mechanical Load	5400 Pa
Wind Load	2400 Pa

**WARRANTY**

10 year Product Workmanship Warranty

25 year Linear Performance Warranty

(Please refer to product warranty for details)

**PACKAGING CONFIGURATION**

Modules per box: 30 pieces

Modules per 40' container: 840 pieces

